

- **Ma** → screw tightening torque (Nm)
- **Mt** → transmissible torque (with Fax = 0) (Nm)
- **Fax** → axial force (with Mt = 0) (kN)
- **Ps** → specific pressure on shaft (N/mm<sup>2</sup>)
- **Ph** → specific pressure on hub (N/mm<sup>2</sup>)
  
- **Ma** → 螺絲鎖緊扭矩 (Nm)
- **Mt** → 傳遞扭矩 (Nm)
- **Fax** → 軸向壓力 (kN)
- **Ps** → 軸面負荷壓力 (N/mm<sup>2</sup>)
- **Ph** → 軸套面負荷壓力 (N/mm<sup>2</sup>)


**SPECIFICATION:**
**TYPE JD**

Dimensions			Screws		Performances				
d x D	L	L1	Size	Ma	Mt	Fax	Ps	Ph	
18 x 47	48	42	M6	17	510	57	322	123	
19 x 47	48	42	M6	17	540	57	305	123	
26 x 47	48	42	M6	17	570	57	290	123	
22 x 47	48	42	M6	17	620	57	263	123	
24 x 50	48	42	M6	17	680	57	241	116	
25 x 50	48	42	M6	17	710	57	232	116	
28 x 55	48	42	M6	17	790	57	207	105	
30 x 55	48	42	M6	17	850	57	193	105	
32 x 60	48	42	M6	17	1,200	76	241	129	
35 x 60	48	42	M6	17	1,300	76	221	129	
38 x 65	48	42	M6	17	1,400	76	203	119	
40 x 65	48	42	M6	17	1,500	76	193	119	
42 x 75	58	50	M8	41	2,200	100	221	124	
45 x 75	58	50	M8	41	2,400	100	206	124	
48 x 80	58	50	M8	41	2,500	100	193	116	
90 x 80	58	50	M8	41	2,600	100	165	116	
55 x 85	58	50	M8	41	3,800	140	225	145	
60 x 90	58	50	M8	41	4,200	140	206	137	
65 x 95	58	50	M8	41	4,500	140	190	130	
70 x 110	70	60	M10	83	7,000	200	190	121	
75 x 115	70	60	M10	83	7,500	200	178	116	
80 x 120	70	60	M10	83	8,000	200	167	111	
85 x 125	70	60	M10	83	9,800	230	179	122	
90 x 130	70	60	M10	83	10,300	230	169	117	
95 x 135	70	60	M10	83	13,600	290	200	141	
106 x 145	80	68	M12	145	15,000	300	173	119	
110 x 155	80	68	M12	145	16,500	300	157	112	
120 x 165	80	68	M12	145	20,600	340	165	120	
130 x 180	80	68	M12	145	27,900	430	190	137	
140 x 190	90	76	M14	230	32,300	460	171	126	
150 x 200	90	76	M14	230	43,200	580	200	150	
160 x 210	90	76	M14	230	46,100	580	167	143	

**ORDERING EXAMPLE:**

圖式 Type	尺寸 Size (d x D)
<b>JD</b>	<b>50 x 80</b>