



FEATURES
(E) TYPE:RJF (WITH CLAMP HUBS) characteristics

This type coupling permits quick, sure fixing without any shaft-hub backlash.
 With the keyless coupling type, the torque applied for tightening down the screws(M_s) must be as given in the table.
 The RJ coupling type is available with or without keyway.

特性
(E) 類型：RJF(有夾鉗輪軸) 性能

此類型的聯軸器可以快速確實的固定，沒有軸-輪軸的背離。
 無鍵槽的聯軸器類型，可使用MS扭力將螺釘向下鎖緊，如表所示。
 RJ類型的聯軸器分有鍵槽及無鍵槽兩種。


SPECIFICATION:
TYPE RJ

TYPE	Fmin (mm)	Fmax (mm)	A (mm)	L (mm)	I (mm)	M (mm)	N (mm)	s (mm)	f	t (mm)	M_s (Nm)	Hub	
												weight(kg)	J(kg/m ³)
ALUMINIUM HUBS 鋁合金調軸殼													
7	3	7	14	22	7	8	6	1.0	M2	3.5	0.35	0.003	0.085 x 10 ⁴
9	4	9	20	30	10	10	8	1.0	M2.5	5	0.75	0.009	0.49 x 10 ⁴
14	6	16	30	35	11	13	10	1.5	M3	5	1.4	0.020	2.8 x 10 ⁴
19/24	10	20	40	66	25	16	12	2.0	M6	12	11	0.066	20.4 x 10 ⁴
24/28	10	28	55	78	30	18	14	2.0	M6	14	11	0.132	50.8 x 10 ⁴
28/38	14	35	65	90	35	20	15	2.5	M8	15	25	0.253	200.3 x 10 ⁴
38/45	15	45	80	114	45	24	18	3.0	M8	20	25	0.455	400.6 x 10 ⁴
STEEL HUBS 合金鋼輪殼													
42	20	45	95	126	50	26	20	3.0	M8	20	25	1.850	2.246 x 10 ⁴
48	25	60	105	140	56	28	21	3.5	M10	22	49	1.850	3.786 x 10 ⁴
55	25	70	120	160	65	30	22	4	M10	22	49	3.800	7.496 x 10 ⁴
65	25	75	135	185	75	35	26	4.5	M10	22	49	4.500	12.000 x 10 ⁴