


**SPECIFICATION:**

TYPE	Fmin (mm)	Fmax (mm)	A (mm)	L (mm)	I (mm)	M (mm)	N (mm)	s (mm)	p (mm)	h	Ms (Nm)	Hub	
												weight(kg)	J(kg/m <sup>3</sup> )
<b>ALUMINIUM HUBS AND STEEL LOCKING ELEMENT 鋁合金軸殼和合金鋼壓力環</b>													
14	6	14	30	50	18.5	13	10	1.5	4	M3	1.3	0.049	0.007 x 10 <sup>9</sup>
19/24	10	20	40	66	25	16	12	2.0	4	M4	2.9	0.120	0.03 x 10 <sup>9</sup>
24/28	15	28	55	78	30	18	14	2.0	4	M5	6	0.280	0.135 x 10 <sup>9</sup>
28/38	19	38	65	90	35	20	15	2.5	5	M5	6	0.450	0.315 x 10 <sup>9</sup>
38/45	20	45	80	114	45	24	18	3.0	5	M6	10	0.950	0.95 x 10 <sup>9</sup>
<b>STEEL HUBS AND LOCKING ELEMENT 合金鋼軸殼和壓力環</b>													
42	28	50	95	126	50	26	20	3.0	5	M8	35	2.300	3.150 x 10 <sup>9</sup>
48	35	60	105	140	56	28	21	3.5	5	M8	35	3.080	5.200 x 10 <sup>9</sup>
55	40	65	120	160	65	30	22	4	5	M10	69	4.670	10.300 x 10 <sup>9</sup>
65	45	70	135	185	75	35	26	4.5	5	M10	120	6.700	19.100 x 10 <sup>9</sup>

**SPECIFICATION:**

TYPE	Recommended M coupling Type Hub Bore Dia. [mm] and Transmissible Torque[Nm]																									
	Ø10	Ø11	Ø14	Ø15	Ø18	Ø17	Ø18	Ø19	Ø20	Ø22	Ø24	Ø25	Ø28	Ø30	Ø32	Ø35	Ø38	Ø40	Ø42	Ø45	Ø48	Ø50	Ø55	Ø60	Ø65	
14	10	12	22	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
19/24	42	46	60	65	69	74	79	84	88	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
24/28	-	-	-	66	72	77	82	87	92	102	113	118	135	-	-	339	-	-	-	-	-	-	-	-	-	-
28/38	-	-	-	-	-	-	-	175	185	205	225	235	266	287	308	471	373	-	-	-	-	-	-	-	-	-
38/45	-	-	-	-	-	-	-	-	255	283	312	325	367	398	427	563	515	545	577	620	-	-	-	-	-	-
42	-	-	-	-	-	-	-	-	-	-	-	-	420	460	500	450	627	670	714	790	850	880	-	-	-	-
48	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	500	600	750	850	1100	1200	1350	1480	-	
55	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1040	1062	1160	1210	1320	1370	1692	1680	
65	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1582	1772	1640	1900	2031	2440	2496	